

Benchmk

SafeGC2065

Empowering Commerce with Speed and Precision

Color Laser Multifunction Printer (MFP)
safeG Series



OPTIONS

1 ENHANCED FEATURES
OCR text recognition LK-105v4
Barcode fonts LK-106
Unicode fonts LK-107
OCR A and B fonts LK-108
Document converter pack LK-110v2
ThinPrint® client LK-111
Serverless pull printing LK-114
Trusted Platform Module LK-115v2
Antivirus LK-116
FOIP activation LK-117



2 CONNECTIVITY	
Fax board FK-514	x2
Wireless LAN UK-221	
USB I/F kit EK-608	OR
USB I/F kit EK-609	
Fiery controller IC-420	
Interface kit for IC-420 VI-516	
Biometric authentication AU-102	OR
Card authentication ID card reader	
Mount kit MK-735	


3 OTHERS
Working table WT-506
Offline Stapler FS-P04
10-Key pad KP-102
Replacement SSD EM-908
Keyboard holder KH-102
Air cleaning unit CU-102

4 MEDIA INPUT	
1x Universal tray PC-116	OR
2x Universal tray PC-216	
Large capacity tray PC-416	OR
Large capacity tray PC-417	
Copier desk DK-516x	OR
Large capacity tray LU-302	
Large capacity tray LU-207	
Banner tray BT-C1e	

5 MEDIA OUTPUT						
Output tray OT-513	OR	Inner finisher FS-542	OR	Staple finisher FS-539	OR	Staple finisher FS-540
		Punch kit for FS-542 PK-527		Relay unit RU-513	OR	Relay unit RU-513
				Booklet finisher FS-539SD		Booklet finisher FS-540SD
				Relay unit RU-513	OR	Relay unit RU-513
				Punch kit for FS-539/SD PK-524		Punch kit for FS-540/SD PK-526
						Post inserter for FS-540/SD PI-507
					OR	Job separator for FS-540/SD JS-602
						Z-fold unit for FS-540/SD ZU-609

LEGEND
 Option
 Mandatory option
 This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES



Corner stapling
 Two-point stapling
 Two-hole punching
 Four-hole punching
 Duplex
 Combined mixplex/mixmedia
 Half-fold
 Sheet insertion
 Letter-fold
 Booklet
 Offset sorting
 Z-fold
 Banner printing
 Corner Stapling (offline)

DESCRIPTION

ENHANCED FEATURES

LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-114 Serverless pull printing	Secure and Follow Me printing solution requiring no server application
LK-115v2 Trusted Platform Module	Trusted Platform Module for protection of data encryption and decryption
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit

CONNECTIVITY

FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
IC-420 Fiery controller	Professional colour print controller
VI-516 Interface kit for IC-420	Fiery controller interface card
AU-102 Biometric authentication	Finger vein scanner
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

OTHERS

WT-506 Working table	Authentication device placement
FS-P04 Offline Stapler	Offline stapler, 20 sheets stapling
KP-102 10-Key pad	For use instead of touchscreen
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard
CU-102 Air cleaning unit	Improving indoor air quality by reduced emission

MEDIA INPUT

PC-116 1x Universal tray	500 sheets, A5-A3, 52-256 g/m ²
PC-216 2x Universal tray	2x 500 sheets, A5-A3, 52-256 g/m ²
PC-416 Large capacity tray	2,500 sheets, A4, 52-256 g/m ²
PC-417 Large capacity tray	1,500 + 1,000 sheets, A5-A4, 52-256 g/m ²
DK-516x Copier desk	Provides storage space for print media and other materials
LU-302 Large capacity tray	3,000 sheets, A4, 52-256 g/m ²
LU-207 Large capacity tray	2,500 sheets, A4-SRA3, 52-256 g/m ²
BT-C1e Banner tray	Multipage banner feeding

MEDIA OUTPUT

OT-513 Output tray	Output tray used instead of finisher
FS-542 Inner finisher	50-sheet stapling, 500 sheets max. output
PK-527 Punch kit for FS-542	2/4 hole punching, autoswitching
FS-539 Staple finisher	50 sheets stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50 sheets stapling; 20 sheets booklet finisher; 2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/4 hole punching; autoswitching
FS-540 Staple finisher	100 sheets stapling; 3,200 sheets max. output
FS-540SD Booklet finisher	100 sheets stapling; 20 sheets booklet finisher; 2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/4 hole punching; autoswitching
RU-513 Relay unit	For FS-539/SD or FS-540/SD installation
JS-602 Job separator for FS-540/SD	Separation of fax output; etc.
PI-507 Post inserter for FS-540/SD	Cover insertion; post finishing
ZU-609 Z-fold unit for FS-540/SD	Z-fold for A3 prints

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

System speed A4	Up to 65/65 ppm (mono/colour)
System speed A3	Up to 32/32 ppm (mono/colour)
Autoduplex speed A4	Up to 65/65 ppm (mono/colour)
1st page out time A4	2.8/3.8 sec. (mono/colour)
Warm-up time	Approx. 12/13 sec. (mono/colour) ¹
Imaging technology	Laser
Toner technology	Polymerised toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour
Automatic document feeder	Up to 300 originals; A6-A3; 35-210 g/m ² ; Dualscan ADF
ADF double feed detection	Standard
Printable paper size	A6-SRA3; customized paper sizes; banner paper max. 1,200 x 297 mm
Printable paper weight	52-300 g/m ²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500; A6-A3; custom sizes; 52-256 g/m ² 1x 500; A5-SRA3; custom sizes; 52-256 g/m ²

SYSTEM SPECIFICATIONS

Paper tray input (optional)	1x 500 sheets; A5-A3; 52-256 g/m ² 2x 500 sheets; A5-A3; 52-256 g/m ² 1x 2,500 sheets; A4; 52-256 g/m ² 1x 1,500 + 1x 1,000 sheets; A5-A4; 52-256 g/m ²
Large capacity tray (optional)	1x 3,000; A4; 52-256 g/m ² 1x 2,500; A4-SRA3; custom sizes; 52-256 g/m ²
Manual bypass	150 sheets; A6-SRA3; custom sizes; banner; 60-300 g/m ²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold; Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	A6-SRA3; 52-256 g/m ²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m ²)
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m ²)
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Duty cycle (monthly)	Rec. 53,000 pages; Max. 250,000 pages
Toner lifetime	Black up to 28,000 pages CMY up to 28,000 pages
Imaging unit lifetime	Black up to 240,000/1,000,000 pages (drum/developer) CMY up to 165,000/1,000,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 2.00 kW
System dimension (W x D x H)	615 x 688 x 961 mm (without options)
System weight	Approx. 100.0 kg (without options)



PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 10 (32/64); Windows 11; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Windows Server 2022; macOS 10.14 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin; Barcode fonts (optional); OCR A and B fonts (optional); Unicode fonts (optional)
Mobile printing	AirPrint (iOS); Mopria (Android); optional: WiFi Direct

PRINTER SPECIFICATIONS (OPTIONAL)

Print controller	Embedded Fiery IC-420 v2
Controller CPU	Intel Celeron G4900T @ 2.9 GHz
Memory/HDD	4,096 MB / 500 GB
Page description language	Adobe PostScript 3 (CPSI 3020); PCL 6; PCL 5c
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows 11; Windows Server 2022; macOS 10.14 or later

SCANNER SPECIFICATIONS

Scan speed	Up to 140/140 ipm in simplex (mono/colour) Up to 280/280 ipm in duplex (mono/colour)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX; PDF/A 1a and 1b optional: Searchable PDF; Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	Max. A3
Magnification	25-400% in 0.1% steps; Auto-zooming



REMAN is derived from the abbreviation of "Remanufacturing." The combination of the REMAN logo and the Earth graphic reflects a global perspective while embodying the brand's commitment to sustainable development. It vividly conveys the brand proposition of "Green Cycle, Value Renewal" and represents Benchmk's steadfast commitment to green, circular, and sustainable office solutions.

sefeGprint—the print management expert (Standard Print Management Software)

aims to help clients solve issues caused by uncontrolled printing—such as paper waste, document security risks, and complex device management—through low-cost and lightweight deployment. It assists enterprise users in reducing costs, improving efficiency, and achieving high-quality development.

Home	Security Management	Job Management	Device Management	Billing Management	User Management	Report Management	System Management	Local Functions	Enhanced Features*
Control Statistics	QR Code Login	Cloud Print	Printer Management	Quota Management	User Management	Device Reports	Device Status	One-Click Switching	Dual-Machine Hot Backup
Job Load Statistics	Job Archiving	Cloud Scan	Authentication Device Management	Department Billing	Department Management	User Reports	Print Volume Display	Silent Driver Installation	High Availability
User Statistics	Facial Recognition	Pick-up Code	Facial Recognition Device Management	Periodic Reset	Domain Synchronization	Department Reports	Supplies Warning	Domain Push Driver	Distributed Deployment
Print Statistics	Card Login	Countdown Job	One-Click Control	Unit Price Management	DingTalk Synchronization	Task Reports	Large Screen Monitoring	Domain Shared Driver	Public Network Roaming
	Smart Watermark	Scan to WEB	Configuration-Free MFP		WeCom (Enterprise WeChat) Synchronization		Email Alert	Quick Login	VPN Management
	PIN Code	Scan to Email	Customizable Interface		Print Permission Control				SDK Integration
	Keyword Audit*	Print Approval*			Domain Authentication				

*Indicates paid optional features

FAX SPECIFICATION

Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication); Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

SYSTEM FEATURES

Security	ISO 15408 Common Criteria; IP filtering and port blocking; SSL3 and TLS1.1/1.2/1.3 network communication; IPsec support; IEEE 802.1x support; User authentication; Authentication log; Secure print; Kerberos; Hard drive overwrite; Hard drive data encryption (AES 256); Confidential fax; Print user data encryption optional: Antivirus realtime scanning (Bitdefender®)
Accounting	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition; Authentication by mobile device (Android) optional: Biometric authentication (finger vein scanner); ID card authentication (ID card reader); Authentication by mobile device (iOS)
Software	Data Administrator; Web Connection; HDD Backup Utility; Driver Packaging Utility; Log Management Utility; Font Management Utility; Download Manager

¹ Warm-up time may vary depending on the operating environment and configuration

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m² quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Benchmk does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

Benchmk Intelligent (Zhongshan) Technology Co., Ltd.

Address: 4/F, Benchmk Building, Tower 1, No. 1 Fuyuan Road, Shenwan Town, Zhongshan City, Guangdong Province, China
Email: bk@benchmk.com
Website: www.benchmk.com

Benchmk Business Systems Vietnam Co., Ltd.

Address: 16, Alley 6/3, Mac Thai To Street, Yen Hoa Ward, Cau Giay District, Hanoi, Vietnam

Benchmk - Ho Chi Minh City Branch

Address: 1A3/257, Group 3, Hoa Lan 2 Quarter, Thuan Giao Ward, Ho Chi Minh City, Vietnam